

Prior to installation

1. To activate the parking watch, gently pull the isolation foil.
2. When 'hours' flickers, press 2 or 3 to set the time. When the hours have been set correctly, press 1.
3. Set the minutes by the same procedure as point 2.
4. Set the year, month and date by the same procedure as point 2.
5. After the time and date have been set correctly, press 1 to exit the setting mode. Now only the ':' symbol will flicker on the inner LCD display.
6. You are now ready to mount the product on the windscreen.
7. The parking watch is factory set to rounding to the nearest forthcoming 15 min. There can be different requirements for setting the parking time in other countries. Change the time interval between 15 and 30 min depending on the parking rules in the relevant country.

Press 2 down for 10 seconds until the display show 15 or 30. Change the setting by clicking on button 2. If you do not activate button 2 for 5 seconds, the setting will be saved and the display will return to normal showing.

- If you choose the setting 15 – The parking watch will set to nearest forthcoming 15 min.

- If you choose the setting 30 – The parking watch will set to nearest forthcoming 30 min.

You can reset the time setting, if needed. Press 1 for 5 seconds and follow the above steps.

NB: We recommend that you check the parking watch's time settings regularly, especially at the transition between summer and winter time.

Mounting

The parking watch must be mounted on the inside of the windscreen. The temperature on the windscreen should not be lower than +15°C. Use the car's air-conditioning to warm up the windscreen if necessary - this will reinforce the adhesive pads.

1. Find the most appropriate place for installation – Remember to follow the laws in your country. Please make sure that you can easily reach the buttons on the back of the parking watch after mounting.
2. Carefully clean the area you have chosen for mounting. Use a damp cloth to remove dust, and then degrease the area with the enclosed cleaning tissue (only the enclosed cleaning tissue should be used). Dry the windscreen with a soft, clean cloth.
3. Remove the protection foil from the four adhesive pads.
4. Place the parking watch on the windscreen and press for at least 30 sec. check from the outside if all of the four adhesive pads are attached to the windscreen.
5. Your parking watch is now mounted and ready for use.

NB: You may only have one parking watch on your windscreen. It is always the responsibility of the driver to ensure that the time and the parking time have been set correctly. Any parking tickets will not be refunded.

If not all dirt and grease is removed from the inside of the wind-screen or if there is a lot of dust in the air when you install the product, the slight 'bubbles/bumps' under the adhesive pads can occur.

Manual setting of the parking time

This function can be used when you park outside the limited parking time. Press 3 to enter the settings for manual parking time. During the manual setting of the parking time the inner LCD display shows the 'hours' and 'minutes' of parking. If the actual time is 12:00, and you press 3 until the parking time on the inner LCD display says 14:00, the large display on the front will also show 14:00.

If you do nothing for 5 sec during the manual setting of the parking time, The parking watch's inner LCD display will show the actual time again.

Maintenance

Avoid exposing the product to very high/low temperatures (≤ -20°C or ≥ +70°C) and avoid rough handling.

If The parking watch is exposed to water, you can dry it with a soft, clean cloth. Do not use detergents to clean the product. Do not disassemble the product, as that would destroy the electronics. For disposal, hand the product in at the nearest recycling plant, so that the materials may be recycled.

Service and warranty

If the inner LCD display shows the letter "E", an operation error has occurred in the parking watch.

A service is required and you have to contact the retailer.

You can also contact us at info@samatech.dk

A warranty is provided according to the Danish Sale of Goods Act, if an error occur during the warranty period, please return the device immediately to your retailer together with a copy of your receipt, which is your certificate of guarantee. Your case will be processed and your parking watch will be repaired or replaced.

Certificates and approvals

FS-mark: The parking watch has been approved by the Danish Road Safety and Transport Agency with reference to order no. 327, 2003 on parking watches.

Hereby declares that this parking watch meets the general safety requirements of the relevant CE – marking directives. This product is in accordance with (CE) EN 50498.



Electrical and Electronic Equipment (WEEE) contains components, materials and substances that can be hazardous to the environment and general health. The product must be disposed correctly. Therefore, it has been marked with an image of a crossed-out dustbin indicating that the product must not be disposed alongside unsorted household waste, but should be collected separately

**Technical specifications**

Size: Ø 104 mm x 18 mm

Clock accuracy (average): ± 1 min./ 1 year

Reaction time (parking mode): approx. 20 sec

Reaction time (out of parking mode): approx. 20 sec